



Start with a better finish!

RSA CLEANSKIN

TECHNICAL DATA SHEET

PRECAUTIONS AND LIMITATIONS

This product should not be applied in windy conditions and in temperatures below 5°C (temperature must be climbing on application and should not fall below 5°C within eight hours of application) or above 35°C. Protect from freezing and temperatures below 5°C for 48 hours after application. Protect from rain for up to 48 hours after application.

When applied, this product cannot be expected to hide imperfections, correct poor quality substrate installations or overcome preparation / workmanship deficiencies.

RSA Cleanskin may appear cloudy / milky if applied too thick.

This product does not have the ability to bridge structural cracks other than micro / hairline cracks.

Substrates and previous RSA coatings must contain less than 15% Wood Moisture Equivalent (WME) prior to the application of RSA Multiprime.

PRODUCT DESCRIPTION

Render Systems Australia Cleanskin is a water based, clear acrylic protective coating which provides a protective and decorative finish over RSA Bling and tinted Polysand 800 texture coatings and systems.

FEATURES AND BENEFITS

- ✓ Increases moisture resistance properties as part of a full acrylic system
- ✓ Enhances and effectively assists with sealing RSA Bling and tinted Polysand 800 texture systems
- ✓ Micro crack and alkali resistant
- ✓ Provides excellent adhesion to all properly prepared substrates
- ✓ Offers excellent flow, leveling and wet edge properties
- ✓ Results in a tough, durable, easy to clean, weather resistant protective coating
- ✓ Hard wearing with good resistance to abrasion

APPLICATION GUIDELINES

1. Ensure the surface is clean, dry and free of all contaminants.
2. The product should be thoroughly mixed before use.
3. Cleanskin should be applied with a 10 - 12mm roller and cut in using a brush. Alternatively, the product can be sprayed for a superior build.
4. Ensure a wet edge is kept when cutting in and rolling RSA Cleanskin.

TINTING AND OVERCOATING

RSA Cleanskin is a clear protective coating which is not to be tinted.



RSA CLEANSKIN

TECHNICAL DATA SHEET

PLEASE NOTE

The information given in this Technical Data Sheet is based on current knowledge of the product when properly stored, handled and applied. We cannot guarantee that the product will be suitable, effective or safe when used for any purpose other than its stated uses.

To the extent that it is lawful, we exclude warranties implied by law and limit our liability to the cost of replacing the product. We accept no responsibility for loss or injury caused by improper use, incompetent preparation, inexpert or negligent application or ordinary wear and tear.

Service or advice given by our staff should not amount to responsibility for the project - since the owner or their contractor (and not River Sands) is responsible for procedures relating to the application of the product.

FURTHER INFORMATION

For further information consult the Material Safety Data Sheet (MSDS) and read the product label carefully before use.

MSDS documents are available by phoning 1800 077 744.

TECHNICAL AND APPLICATION DATA

Colour Bases	Clear Only
Coverage	One 15 litre pail will cover approximately 200m ²
Toxicity	Lead free and dry film is non-toxic and conforms with AS 1647
Application	10 - 12mm Nap Roller or Spray Gun
Thinning	Do not thin RSA Cleanskin
Dry Time	Please refer to the Application Guidelines for relevant substrate & product
Abrasion Resistance	Very Good
Wet Film Thickness	Approximately 60 microns
Dry Film Thickness	Approximately 22 microns
Shelf Life	Two years when stored in a cool, dry environment
Coats	1 - 2 coats
Flammability	Non-flammable
Clean up	Protect all areas not to be coated and clean with potable water

TRANSPORT AND STORAGE

Packaging Type	15 litre plastic pails
Pail Weight	19.5kg
Pails Per Pallet	48
Dangerous Goods	n/a

WARRANTY

Render Systems Australia (RSA) offers a 7 Year Product Warranty provided:

1. All substrates are installed in accordance with manufacturers specifications, Australian Standards and Good Trade Practices.
2. All products and processes as detailed above are applied by an RSA preferred contractor and in accordance with RSA Technical Data Sheets, Specifications, Application Guidelines and Good Trade Practices.
3. Guidelines Only - always refer to RSA System Specifications and Application Guidelines.

RSA strongly recommend viewing a physical product sample prior to selection of finish and colour.



For more information call Head Office: **07 3412 8111** Toll Free: **1800 077 744**
www.renderystemsaustralia.com.au